

STEEL STRAPPING

Sterling Chemical supply Steel Strapping is manufactured from a mild-carbon steel to meet customer's requirement. Our steel strapping are perfect for packaging and bundling brick, concrete block, refractory brick and many other products.

Strapping Size		Finished		Coil Winding	
Width (mm)	Thickness (mm)	Blue Tempered	Painted & waxed	Ribbon type	Oscillated type
12.7	0.36	√	√	√	√
12.7	0.40	√	√	√	√
12.7	0.50	√	√	√	√
16.0	0.36	√	√	√	√
16.0	0.40	√	√	√	√
16.0	0.50	√	√	√	√
16.0	0.60	√	√	√	√
16.0	0.65	√	√	√	√
19.0	0.50	√	√	√	√
19.0	0.60	√	√	√	√
19.0	0.65	√	√	√	√
19.0	0.70	√	√	√	√
19.0	0.80	√	√	√	√
19.0	0.90	√	√	√	√
19.0	0.70	√	√	√	√
19.0	0.80	√	√	√	√
19.0	0.90	√	√	√	√

Steel Quality : Chinese standard Q235 equivalent to Germany standard st37.2

Breaking Strength : $\sigma_b \geq 780-900$ MPa

Elongation : $\delta_5 \geq 3\% - 5\%$